

DC Output, Wall Plug-In and DeskTop

Part Number Ordering System (See Page 278)
Output Plug/Cord Options (See Page 247)



General Specifications: Input Voltage/ Frequency:

230VAC+/-10%/50Hz for Euro.Type Models
240VAC+/-10%/50Hz for Australia, UK Type Models

Output VoltageTolerance:

+/-5% at full load

Protection:

Primary Thermal Fuse

Configuration:

Step Down Line Transformer with Rectifier-Capacitor
Filter, Euro./U.K./Australia (SAA) Type Wall Plug-in
or DeskTop Dual Cord In/ Out

Operating Temperature:

0° to 40° C

Humidity:

0% to 90% R.H., non-condensing

Storage Temperature:

-20° to 70° C

Dielectric Strength:

2500VAC pri-sec
2500VAC pri-ground / 500VAC sec-ground (option)

Enclosure:

Black Polycarbonate, UL94V-0

Cooling:

Thermal Convection, no-vents

Cords:

Output: Standard, 6ft. 2 conductor, 24-18AWG;
Input: 2 or 3 conductor, (DeskTop)
For other output cords, please refer to Output
Plug/Cord Options

Safety:

All Models are TUV/GS approved to EN60950;
TUV Subscriber #41405
Australian Models comply with AS/NZS 3108

EMI:


CE Compliant

Notes:

- 1) For unit size and output cords please refer to Adaptors Case Style and Adaptors Output Plug/Cord Options.
 - 2) For Input Blade Options please refer to International Adaptor for Input Blade Options
 - *3) Within each Model, Output Current may vary from 50mA to max load specified in 50mA increments pre serving output voltage +/-5% Tolerance
 - **4) Optional for specifying Output Voltage Deviation from Standard Model add Suffix -x.x to Model No.
- Unit Size Codes:**
GT-3 Models EI 35,41,48,57,60,66: Transformer Core Size:
Options:
- 1) Primary earth ground pin and secondary/shield ground
 - 2) Custom output cords, connectors and shielding attachments
 - 3) Other outputs or custom design per customer specifications

Schematic Diagram:

AC Input:
220/230/240VAC
50Hz



DC Output:
3.0VDC-30VDC
50mA-2000mA



Model Selection Road Map Example:

1. Required: ITE EN60950 9VDC / 700mA, EURO. "2" Prong Plug, Wall Plug-In, Output Plug Center Positive 2.5mm ID Barrel.
2. Selection table presented in increasing output voltage order; page 3: locate 9VDC/700mA: GT-3T-4B-9-700D
3. Model Selected: GT-3T-4B-9-700D w/ case Size EI-48; Please refer to Adaptors Case Style.
4. Output Plug/Cord selected "L-"; Please refer to Adaptors Plug/Cord Options

** MODEL NUMBER	OUTPUT (VDC)	* MAX CURRENT (MA)	CASE SIZE	EURO. WALL PLUG (E)	U.K. WALL PLUG (B)	SAA WALL PLUG (S)	EURO DESKTOP	U.K. DESKTOP	SAA DESKTOP
GT-3T35-3-200C	3.0	200	EI-35	■	■				
GT-3T35-3-300C	3.0	300	EI-35	■	■				
GT-3T35-3-400C	3.0	400	EI-35	■	■				
GT-3T41-3-1000D	3.0	1000	EI-41	■	■		■	■	
GT-3T41-4-1000D	4.0	1000	EI-41	■	■		■	■	
GT-3T41-4-1300D	4.0	1300	EI-41	■	■		■	■	
GT-3T48-4-1500D	4.0	1500	EI-48	■	■		■	■	
GT-3T35-4.5-500C	4.5	500	EI-35	■	■				
GT-3T41-4.5-600C	4.5	600	EI-41	■	■		■	■	
GT-3T41-4.5-800C	4.5	800	EI-41	■	■		■	■	
GT-3T35-5.8-180B	6.0	180	EI-35	■	■				
GT-3T35-6-50C	6.0	50	EI-35	■	■				

SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.



Part Number Ordering System (See Page 278)
Output Plug/Cord Options (See Page 247)



** MODEL NUMBER	OUTPUT (VDC)	* MAX CURRENT (MA)	CASE SIZE	EURO. WALL PLUG (E)	U.K. WALL PLUG (B)	SAA WALL PLUG (S)	EURO DESKTOP	U.K. DESKTOP	SAA DESKTOP
GT-3T35-6-100C	6.0	100	EI-35	■	■				
GT-3T35-6-150C	6.0	150	EI-35	■	■				
GT-3T35-6-200C	6.0	200	EI-35	■	■				
GT-3T35-6-250C	6.0	250	EI-35	■	■				
GT-3T35-6-300C	6.0	300	EI-35	■	■				
GT-3T35-6-350C	6.0	350	EI-35	■	■				
GT-3T41-6-400C	6.0	400	EI-41	■	■		■	■	
GT-3T41-6-500C	6.0	500	EI-41	■	■		■	■	
GT-3T41-6-600D	6.0	600	EI-41	■	■		■	■	
GT-3T41-6-800D	6.0	800	EI-41	■	■		■	■	
GT-3T48-6-1000D	6.0	1000	EI-48	■	■		■	■	
GT-3T48-6-1200D	6.0	1200	EI-48	■	■		■	■	
GT-3T57-6-1200D	6.0	1200	EI-57	■	■		■	■	
GT-3T57-6-1500D	6.0	1500	EI-57	■	■		■	■	
GT-3T35-7.2-200B	7.2	200	EI-35	■	■		■	■	
GT-3T48-7.2-850B	7.2	850	EI-48	■			■		
GT-3T35-7.5-200C	7.5	200	EI-35	■	■	■			
GT-3T35-7.5-250C	7.5	250	EI-35	■	■				
GT-3T35-7.5-300C	7.5	300	EI-35	■	■				
GT-3T41-7.5-400C	7.5	400	EI-41	■	■		■	■	
GT-3T41-7.5-500D	7.5	500	EI-41	■	■		■	■	
GT-3T41-7.5-700D	7.5	700	EI-41	■	■		■	■	
GT-3T48-7.5-900D	7.5	900	EI-48	■	■		■	■	
GT-3T48-7.5-1000D	7.5	1000	EI-48	■	■		■	■	
GT-3T48-7.5-1200D	7.5	1200	EI-48	■	■		■	■	
GT-3T57-7.5-1200D	7.5	1200	EI-57	■	■		■	■	
GT-3T57-7.5-1500D	7.5	1500	EI-57	■	■		■	■	
GT-3T60-7.5-2900D	7.5	2900	EI-60				■	■	
GT-3T35-8-200B	8.0	200	EI-35	■					
GT-3T41-8-350C	8.0	350	EI-41	■	■		■	■	
GT-3T48-8.7850B	8.7	850	EI-48	■			■	■	
GT-3T35-9-50C	9.0	50	EI-35	■	■				
GT-3T35-9-100C	9.0	100	EI-35	■	■				
GT-3T35-9-150C	9.0	150	EI-35	■	■				
GT-3T35-9-200C	9.0	200	EI-35	■	■				
GT-3T41-9-250C	9.0	250	EI-41			■	■	■	■
GT-3T35-9-300C	9.0	300	EI-35	■	■				
GT-3T41-9-300C	9.0	300	EI-41	■	■		■	■	
GT-3T41-9-300D	9.0	300	EI-41			■	■	■	■
GT-3T41-9-350D	9.0	350	EI-41	■	■		■	■	
GT-3T41-9-400D	9.0	400	EI-41	■	■		■	■	
GT-3T41-9-450D	9.0	450	EI-41	■	■		■	■	

SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.

DC Output, Wall Plug-In and DeskTop

Part Number Ordering System (See Page 278)
Output Plug/Cord Options (See Page 247)


** MODEL NUMBER	OUTPUT (VDC)	* MAX CURRENT (MA)	CASE SIZE	EURO. WALL PLUG (E)	U.K. WALL PLUG (B)	SAA WALL PLUG (S)	EURO DESKTOP	U.K. DESKTOP	SAA DESKTOP
GT-3T41-9-500D	9.0	500	EI-41	■	■	■	■	■	■
GT-3T41-9-600D	9.0	600	EI-41	■	■		■	■	
GT-3T41-9-650D	9.0	650	EI-41	■	■		■	■	
GT-3T48-9-700D	9.0	700	EI-48	■	■		■	■	
GT-3T48-9-800D	9.0	800	EI-48	■	■		■	■	
GT-3T48-9-900D	9.0	900	EI-48	■	■		■	■	
GT-3T48-9-1000D	9.0	1000	EI-48	■	■		■	■	
GT-3T48-9-1200D	9.0	1200	EI-48	■	■		■	■	
GT-3T48-10-550D	10.0	500	EI-48	■	■		■	■	
GT-3T48-10-700D	10.0	700	EI-48	■	■		■	■	
GT-3T48-10-850D	10.0	850	EI-48	■	■		■	■	
GT-3T35-11.6-180B	11.6	180	EI-35	■	■				
GT-3T41-11.8-300C	11.8	300	EI-41			■			■
GT-3T35-12-50C	12.0	50	EI-35	■	■				
GT-3T35-12-100C	12.0	100	EI-35	■	■				
GT-3T35-12-120C	12.0	120	EI-35	■	■				
GT-3T35-12-150C	12.0	150	EI-35	■	■				
GT-3T35-12-200C	12.0	200	EI-35	■	■				
GT-3T41-12-200C	12.0	200	EI-41	■	■		■	■	■
GT-3T41-12-250C	12.0	250	EI-41				■	■	■
GT-3T41-12-300C	12.0	300	EI-41	■	■		■	■	
GT-3T41-12-400D	12.0	400	EI-41	■	■		■	■	
GT-3T41-12-500D	12.0	500	EI-41	■	■		■	■	
GT-3T48-12-700D	12.0	700	EI-48	■	■		■	■	
GT-3T48-12-800D	12.0	800	EI-48	■	■		■	■	
GT-3T48-12-900D	12.0	900	EI-48	■	■		■	■	
GT-3T48-12-1000D	12.0	1000	EI-48	■	■		■	■	
GT-3T48-12-1200D	12.0	1200	EI-48	■	■		■	■	
GT-3T48-13.5-850D	13.5	850	EI-48	■	■		■		
GT-3T48-13.5-1000D	13.5	1000	EI-48	■	■		■		
GT-3T41-14-350D	14.0	350	EI-41	■	■	■	■	■	
GT-3AT41-14-350D	14.0	350	EI-41			■		■	
GT-3T48-14-850D	14.0	850	EI-48	■	■	■	■	■	
GT-3T57-15-800D	15.0	800	EI-57	■	■		■		
GT-3T48-16-500D	16.0	500	EI-48	■			■		
GT-3T35-18-150C	18.0	150	EI-35	■	■				
GT-3T57-20-750D	20.0	750	EI-57	■	■		■		
GT-3T57-20-900D	20.0	900	EI-57	■	■		■		
GT-3T35-22-100D	22.0	100	EI-35	■	■				
GT-3T48-24-400D	24.0	400	EI-48	■			■		
GT-3T48-24-550D	24.0	550	EI-48	■	■		■		
GT-8T35-28-100D	28.0	100	EI-35	■					



SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE. CONSULT GLOBTEK CUSTOMER SERVICE FOR LATEST SPECIFICATIONS.



 INDOOR USE ONLY



** MODEL NUMBER	OUTPUT (VDC)	* MAX CURRENT (MA)	CASE SIZE	EURO. WALL PLUG (E)	U.K. WALL PLUG (B)	SAA WALL PLUG (S)	EURO DESKTOP	U.K. DESKTOP	SAA DESKTOP
GT-3T57-30-500D	30.0	500	EI-57			■		■	
GT-3T57-30-500D	30.0	550	EI-57	■			■		

* APPROVED FOR OUTDOOR USE